RMS ROLLER MILLS

ABM EQUIPMENT

Achieve the most consistent grinds with the least noise and dust.



RMS mills are known by brewers as the most reliable and long-lasting solutions in the sector. The sturdy design and tight controls allow you to crack all grains grains consistently with minimal variance.

When combined with chain disks, the RMS mills can maintain a nearly dust-free environment without the need for dust collection or constant cleaning.

MAX THROUGHPUT	1-PAIR	2-PAIR
20 LBS./MIN	6 x 6	N/A
50 LBS./MIN	9 x 6	9 x 6
83 LBS./MIN	9 x 12	9 x 12
167 LBS./MIN	9 x 18	9 x 18

RMS mills are available in single and double-pairs, depending on the level of desired control. See back for specs.







13911 NW 3rd Ct. Vancouver WA

ABMBrewery.com

FrontDesk@ABMEquipment.com

SPECS



MICRO

- 1/3HP motor
- 1-Phase
- 110/230V
- 3.0 Amps at 230V
- 1.6 Amps at 110V
- 21 1/16” L x 21 3/16” W x 52 1/16” H
- 500 lbs./hr capacity
- Stand
- Customer choice of discharge
- Motor starter & starter enclosure
- ~~Magnet system~~
- Maintenance package



9x6 SINGLE

- 3HP motor
- 3-Phase
- 230/460V at 60HZ
- 8.2 Amps at 230V
- 4.1 Amps at 460V
- 74 7/8” W x 90 1/2” D x 65 11/16” H
- 3,000 lbs./hr capacity
- Stand
- Customer choice of discharge
- Motor starter & starter enclosure
- Magnet system
- Maintenance package



9x6 DOUBLE

- Two 3HP motors
- 3-Phase
- 230/460V at 60HZ
- 8.2 Amps at 230V ea.
- 4.1 Amps at 460V ea.
- 74 7/8” W x 90 1/2” D x 77 11/16” H
- 3,000 lbs./hr capacity
- Stand
- Customer choice of discharge
- Motor starter & starter enclosure
- Magnet system
- Maintenance package

9x12 SINGLE

- 3HP motor
- 3-Phase
- 230/460V at 60HZ
- 8.2 Amps at 230V
- 4.1 Amps at 460V
- 80 7/8” W x 90 1/2” D x 65 11/16” H
- 5,000 lbs./hr capacity
- 9x12 Stand
- Customer choice of discharge
- Motor starter & starter enclosure
- Magnet system
- Maintenance package

9x12 DOUBLE

- Two 3HP motors
- 3-Phase
- 230/460V at 60HZ
- 8.2 Amps at 230V
- 4.1 Amps at 460V
- 80 7/8” W x 90 1/2” D x 77 11/16” H
- 5,000 lbs./hr capacity
- Stand
- Customer choice of discharge
- Motor starter & starter enclosure
- Magnet system
- Maintenance package



6x6 SINGLE

- 1HP motor
- 3-Phase
- 230/460V at 60HZ
- 3.0 Amps at 230V
- 1.5 Amps at 460V
- 28 ¾” L x 25 3/16” W x 58” H
- 1,200 lbs./hr capacity
- Stand
- Customer choice of discharge
- Motor starter & starter enclosure
- Magnet system
- Maintenance package

9x18 SINGLE

- 5HP motor
- 3-Phase
- 230/460V at 60HZ
- 13.2 Amps at 230V
- 6.6 Amps at 460V
- 80 7/8” W x 90 1/2” D x 65 11/16” H
- 10,000 lbs./hr capacity
- Stand
- Customer choice of discharge
- Motor starter & starter enclosure
- Magnet system
- Maintenance package

9x18 DOUBLE

- Two 5HP motors
- 3-Phase
- 230/460V at 60HZ
- 13.2 Amps at 230V
- 6.6 Amps at 460V
- 86 7/8” W x 90 1/2” D x 77 11/16” H
- 10,000 lbs./hr capacity
- Stand
- Customer choice of discharge
- Motor starter & starter enclosure
- Magnet system
- Maintenance package